

Product Usage and Storage Guide

1. Product transportation packaging and storage.

- a) Aluminum foil bags or iron buckets are used for product transportation. For special packaging, please contact Wiseno for negotiation and customization.
- b) The outer package will be marked with: product name, manufacturer name, address, trademark, product quantity, weight, date of manufacture (or batch number), and expiration date.
- c) The signs for receipt and delivery of the outer packaging comply with the relevant regulations and the shipping mark can be accustomed to customer requirements.
- d) Products should be kept in dry, clean, and chemical-free warehouses. The recommended environment is a temperature of 25 degrees Celsius and a humidity of 60%. Prevent contact with acid and alkali substances. Protect the outer packaging from being damaged. Avoid sunlight and rain and snow, moisture-proof, and fire-proof.

2. Product usage guide

- a) Before using this product, please ensure that the packaged product is placed in the production line workshop for at least 12 hours so that the product can be adjusted to the workshop temperature. This will avoid humidity condensation due to changes in ambient temperature when the product is put into production line processing.
- b) This product is suitable for use in a normal dry environment. The recommended processing environment is 25 degrees Celsius and 40% humidity.
- c) The shelf life of the unopened product is 18 months. In order to achieve the best use efficiency of the product, please use it within 18 months. The outer packaging should normally be unpacked just before use and please used up as soon as possible after unpacking.
- d) It is recommended to use a smaller reel diameter to make sure the exposure area is smaller.
- e) The heat-sealing temperature adjustment of the product should be determined according to the machine used for packaging. If you need to provide after-sales technical guidance, please consult local sales.