WisePouch+



WisePouch+

Desiccant Pouch/ Aluminum Desiccant Pouch



Excellent moisture absorption and moisture resistance ability.



Maintain product quality, effectively extending product shelf life.



A multi-layer structure with strong puncture resistance.



No need for desiccant dispensing during production, improves efficiency.



Digital printing and ink printing are available.


WisePouch+ is a functional pre-made pouch made of WiseFlex+ film series. The aluminum pouch with a desiccant layer can absorb and control moisture inside the pouch, effectively extending the shelf life of the product in limited space.

WisePouch+ pouches are suitable for various scenarios and can be made into different types of pouches according to different needs. Fin seal, three-sided seal, stand-up pouches, and ton bags can all be made with WisePouch+. Using WisePouch+ eliminates the need to add desiccant sachets, saving space in packaging and improving production efficiency.

SPECIFICATION:

Take Standard Structure of WisePouch	+ (PET12/Alu12/Des60um) as Example
Thickness (um\mil)	85±8\3.346±0.315
Grammage (g/m²\oz/yd²)	115.0±10.0\3.3928±0.2950
Length (mm\in)	Customizable
Width (mm\in)	Customizable
Binding Width (mm\in)	Customizable
Printing	Available in digital or ink printing
Pouch Type	Provide with different shapes: 3 side seal pouches, stick pack, etc.
Moisture Adsorption Capacity(*MS Des) (25°C, RH40%) (g/m²\oz/yd²)	≥4.0\0.14
Hot tack strength (N/15mm\lb/in)	≥6.0\2.25
Peel strength (N/15mm\lb/in)	≥6.0\2.25
Water vapor transmission rate (38°C,RH90%)(g/(m²-24h))	≤0.015
Oxygen transmission rate (23±2°C)(cm³/(m² ·24h·0.1Mpa))	≤0.015
	*Based on MS Desiccant fil

Shapes to choose:









WiseSorbent Technology LLC

11 E Stow Rd, Marlton, NJ 08053, USA

wisesorbent.com

140 Rue du Canal du Midi - ZAC de La Masquere, 31750 Escalquens - France

wisesorbent.com.fr

No. 8 Lorong Jalak, Kawasan Perusahaan Kebun Baru, Batu 9, 42500 Telok Panglima Garang, Selangor, Malaysia info@wisesorbent.com

