

Technical Data Specification Sheet

Flash Spun HDPE Packed 0.5g Silica Gel Desiccant

| | | | |
|---------------------------|---|------------|--------|
| Product | Flash Spun HDPE Packed 0.5g Silica Gel Desiccant | | |
| Product Code | 1SG-0.5A-ND0EU | | |
| Raw Material | Silica Gel | | |
| Packaging Material | Flash Spun HDPE | | |
| Technical Standard | Water Content (180°C) | | ≤3.0% |
| | Moisture Absorption Capacity 25±2°C RH=20±2% | | ≥9.5% |
| | | RH=50±2% | ≥22.0% |
| | | RH=90±2% | ≥34.0 |
| Sachet Dimension | Weight: | 0.50~0.65g | |
| | Width: | 16±1mm | |
| | Length: | 34±1mm | |
| Sealing Method | Ultrasonic Sealing | | |
| Lasering | Wisemini | | |
| STD Packaging | — 10,000pcs/PE/tin 20,000pcs/2 tins/carton Carton Size: 540×275×325mm, 24ctns/pallet —Carton label contains the following: PO Number Product Name Specification Quantity Batch Number | | |
| Storage | Shelf life: 3 years Desiccant must always be kept in airtight containers to avoid moisture. | | |
| Notes | The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation. | | |

1/20/2025

