

Technical Data Specification Sheet

Flash Spun HDPE Packed 10g Silica Gel Desiccant

| Product | Flash Spun HDPE Packed 10g Silica Gel Desiccant | | | |
|-----------------------|--|-------------------------------|--|-----------------|
| Product Code | 1SG-10A-ND0EU | | | |
| Raw Material | Silica Gel | | | |
| Packaging Material | Flash Spun HDPE | | | |
| Technical Standard | Water Content (180°C) $\leq 3.0\%$ Moisture Absorption Capacity $25\pm2^{\circ}C$ RH= $20\pm2\%$ $\geq 9.5\%$ RH= $50\pm2\%$ $\geq 22.0\%$ RH= $90\pm2\%$ ≥ 34.0 | | | ≥9.5% ≥22.0% |
| Sachet Dimension | Weight: Width: Length: | 9.5~11.0g 38±1mm 90±4mm | | |
| Sealing Method | Ultrasonic Sealing | | | |
| Lasering | Wisemini | | | |
| STD Packaging | 800pcs/PE/tin 1,600pcs/2 tins/carton Carton Size: 540×275×325mm, 24ctns/pallet Carton label contains the following: PO Number Product Name Specification Quantity Batch Number | | | |
| Storage | Shelf life: 3 years Desiccant must always be kept in airtight containers to avoid moisture. | | | |
| Notes | The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation. | | | |

1/20/2025