

## **Technical Data Specification Sheet**

## Flash Spun HDPE Packed 2g Silica Gel Desiccant

Product	Flash Spun HDPE Packed 2g Silica Gel Desiccant			
Product Code	1SG-2A-ND0EU			
Raw Material	Silica Gel			
Packaging Material	Flash Spun HDPE			
Technical Standard	Water Content (180°C) $\leq 3.0\%$ Moisture Absorption Capacity $25\pm2^{\circ}C$ RH= $20\pm2\%$ $\geq 9.5\%$ RH= $50\pm2\%$ $\geq 22.0\%$ RH= $90\pm2\%$ $\geq 34.0$			≥9.5% ≥22.0%
Sachet Dimension	Weight: Width: Length:	2.0~2.3g 22±1mm 52±2mm		
Sealing Method	Ultrasonic Sealing			
Lasering	Wisemini			
STD Packaging	<ul> <li>3,000pcs/PE/tin 6,000pcs/2 tins/carton Carton Size: 540×275×325mm, 24ctns/pallet</li> <li>Carton label contains the following: PO Number</li> <li>Product Name</li> <li>Specification</li> <li>Quantity</li> <li>Batch Number</li> </ul>			
Storage	Shelf life: 3 years Desiccant must always be kept in airtight containers to avoid moisture.			
Notes	The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.			

1/20/2025